ROG STRIX XG279CNS

USER GUIDE

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

ASUS

First Edition

January 2025

Copyright © 2025 ASUSTeK COMPUTER INC. All Rights Reserved.

No part of this manual, including the products and software described in it, may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form or by any means, except documentation kept by the purchaser for backup purposes, without the express written permission of ASUSTeK COMPUTER INC. (“ASUS”).

Product warranty or service will not be extended if: (1) the product is repaired, modified or altered, unless such repair, modification or alteration is authorized in writing by ASUS; or (2) the serial number of the product is defaced or missing.

ASUS PROVIDES THIS MANUAL “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ASUS, ITS DIRECTORS, OFFICERS, EMPLOYEES OR AGENTS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING DAMAGES FOR LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OR DATA, INTERRUPTION OF BUSINESS AND THE LIKE), EVEN IF ASUS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES ARISING FROM ANY DEFECT OR ERROR IN THIS MANUAL OR PRODUCT.

SPECIFICATIONS AND INFORMATION CONTAINED IN THIS MANUAL ARE FURNISHED FOR INFORMATIONAL USE ONLY, AND ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE, AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY ASUS. ASUS ASSUMES NO RESPONSIBILITY OR LIABILITY FOR ANY ERRORS OR INACCURACIES THAT MAY APPEAR IN THIS MANUAL, INCLUDING THE PRODUCTS AND SOFTWARE DESCRIBED IN IT.

Products and corporate names appearing in this manual may or may not be registered trademarks or copyrights of their respective companies, and are used only for identification or explanation and to the owners’ benefit, without intent to infringe.

Contents

Notices ..... **iv**
Safety information ..... **v**
Care & Cleaning ..... **vi**
Takeback Services ..... **vii**
Product information for EU energy label ..... **vii**

Chapter 1: Product introduction

1.1 Welcome! **1-1**
1.2 Package contents **1-1**
1.3 Monitor introduction **1-2**
1.3.1 Front/side view 1-2
1.3.2 Back view 1-3
1.3.3 Other Function(s) 1-4

Chapter 2: Setup

2.1 Assembling the monitor arm/base **2-1**
2.2 Cable management **2-1**
2.3 Adjusting the monitor **2-2**
2.4 Detaching the arm (for VESA wall mount) **2-3**
2.5 Connecting the cables **2-4**
2.6 Turning on the monitor **2-4**

Chapter 3: General instructions

3.1 OSD (On-Screen Display) menu **3-1**
3.1.1 How to reconfigure 3-1
3.1.2 OSD function introduction 3-2
3.2 Specifications summary **3-9**
3.3 Outline dimensions **3-11**
3.4 Troubleshooting (FAQ) **3-12**
3.5 Supported operating mode **3-13**

Notices

Federal Communications Commission Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference, and
- This device must accept any interference received including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



The use of shielded cables for connection of the monitor to the graphics card is required to assure compliance with FCC regulations. Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

Canadian Department of Communications Statement

This digital apparatus does not exceed the Class B limits for radio noise emissions from digital apparatus set out in the Radio Interference Regulations of the Canadian Department of Communications.

This class B digital apparatus complies with Canadian ICES-003.

This Class B digital apparatus meets all requirements of the Canadian Interference - Causing Equipment Regulations.

Cet appareil numérique de la classe B respecte toutes les exigences du Réglement sur le matériel brouiller du Canada.

EAC


Safety information

- Before setting up the monitor, carefully read all the documentation that came with the package.
- To prevent fire or shock hazard, never expose the monitor to rain or moisture.
- Never try to open the monitor cabinet. The dangerous high voltages inside the monitor may result in serious physical injury.
- If the power supply is broken, do not try to fix it by yourself. Contact a qualified service technician or your retailer.
- Before using the product, make sure all cables are correctly connected and the power cables are not damaged. If you detect any damage, contact your dealer immediately.
- Slots and openings on the back or top of the cabinet are provided for ventilation. Do not block these slots. Never place this product near or over a radiator or heat source unless proper ventilation is provided.
- The monitor should be operated only from the type of power source indicated on the label. If you are not sure of the type of power supply to your home, consult your dealer or local power company.
- Use the appropriate power plug which complies with your local power standard.
- Do not overload power strips and extension cords. Overloading can result in fire or electric shock.
- Avoid dust, humidity, and temperature extremes. Do not place the monitor in any area where it may become wet. Place the monitor on a stable surface.
- Unplug the unit during a lightning storm or if it will not be used for a long period of time. This will protect the monitor from damage due to power surges.
- Never push objects or spill liquid of any kind into the slots on the monitor cabinet.
- To ensure satisfactory operation, use the monitor only with UL listed computers which have appropriate configured receptacles marked between 100-240V AC.
- If you encounter technical problems with the monitor, contact a qualified service technician or your retailer.
- Adjustment of the volume control as well as the equalizer to other settings than the center position may increase the ear-/headphones output voltage and therefore the sound pressure level.
- Ensure to connect the power cord to a socket-outlet with earthing connection.
- The supplied power adapter and/or power cable are designed to use with the product only. Do not use with other products.



This symbol of the crossed out wheeled bin indicates that the product (electrical, electronic equipment, and mercury-containing button cell battery) should not be placed in municipal waste. Please check local regulations for disposal of electronic products.

New Mexico PFAS Labeling



AEEE yönetmeliğine uygundur

Care & Cleaning

- Before you lift or reposition your monitor, it is better to disconnect the cables and power cord. Follow the correct lifting techniques when positioning the monitor. When lifting or carrying the monitor, grasp the edges of the monitor. Do not lift the display by the stand or the cord.
- Cleaning. Turn your monitor off and unplug the power cord. Clean the monitor surface with a lint-free, non-abrasive cloth. Stubborn stains may be removed with a cloth dampened with mild cleaner.
- Avoid using a cleaner containing alcohol or acetone. Use a cleaner intended for use with the monitor. Never spray cleaner directly on the screen, as it may drip inside the monitor and cause an electric shock.

The following symptoms are normal with the monitor:

- The screen may flicker during the initial use due to the nature of the fluorescent light. Turn off the Power Switch and turn it on again to make sure that the flicker disappears.
- You may find slightly uneven brightness on the screen depending on the desktop pattern you use.
- When the same image is displayed for hours, an afterimage of the previous screen may remain after switching the image. The screen will recover slowly or you can turn off the Power Switch for hours.
- When the screen becomes black or flashes, or cannot work anymore, contact your dealer or service center to fix it. Do not repair the screen by yourself!

Conventions used in this guide


WARNING: Information to prevent injury to yourself when trying to complete a task.


CAUTION: Information to prevent damage to the components when trying to complete a task.


IMPORTANT: Information that you MUST follow to complete a task.


NOTE: Tips and additional information to aid in completing a task.

Where to find more information

Refer to the following sources for additional information and for product and software updates.

1. **ASUS websites**
   The ASUS websites worldwide provide updated information on ASUS hardware and software products. Refer to http://www.asus.com

2. **Optional documentation**
   Your product package may include optional documentation that may have been added by your dealer. These documents are not part of the standard package.

3. **About Flicker**
   https://www.asus.com/Microsite/display/eye_care_technology/

Takeback Services

ASUS recycling and takeback programs come from our commitment to the highest standards for protecting our environment. We believe in providing solutions for our customers to be able to responsibly recycle our products, batteries and other components as well as the packaging materials.

Please go to http://csr.asus.com/english/Takeback.htm for detail recycling information in different region.

Product information for EU energy label

XG279CNS

1.1 Welcome!

Thank you for purchasing the ROG gaming monitor!

The latest widescreen LCD monitor from ASUS provides a broader, brighter and crystal-clear display, plus a host of features that enhance your viewing experience.

With these features, you can enjoy the convenience and delightful visual experience that the monitor brings to you!

1.2 Package contents

Check your package for the following items:

- ✓ LCD monitor
- ✓ Monitor base
- ✓ Quick start guide
- ✓ Warranty card
- ✓ Power cord
- ✓ DisplayPort cable (optional)
- ✓ HDMI cable (optional)
- ✓ USB Type-C cable (optional)
- ✓ ROG sticker
- ✓ ROG pouch




If any of the above items is damaged or missing, contact your retailer immediately.



If you need to replace the power cord or the connection cable(s), please contact ASUS customer service.

1.3 Monitor introduction

1.3.1 Front/side view



1. ☰ (◈ 5-way) button:
   - Turns on the OSD menu. Enacts the selected OSD menu item.
   - Increases/Decreases values or moves your selection up/down/left/right.
   - Turns on the OSD menu when the monitor enters standby mode or displays the “NO SIGNAL“ message.
   - Move and hold the button downward for over 5 seconds to enable/disable the Key Lock function.
2. ✕ button
   - Exits the OSD menu item.
   - Turns on the OSD menu when the monitor enters standby mode or displays the “NO SIGNAL“ message.
3. ↗1 Shortcut 1 button:
   - Default: GamePlus.
   - To change the shortcut function, go to the MyFavorite > Shortcut > Shortcut 1 menu.
   - Turns on the OSD menu when the monitor enters standby mode or displays the “NO SIGNAL“ message.
4. ↗2 Shortcut 2 button:
   - Default: GameVisual.


- To change the shortcut function, go to the MyFavorite > Shortcut > Shortcut 2 menu.
- Turns on the OSD menu when the monitor enters standby mode or displays the “NO SIGNAL“ message.

5. Power button/power indicator
   - Turns the monitor on/off.
   - The color definition of the power indicator is as the below table.

Status	Description
White	ON
Amber	Standby mode/No signal
OFF	OFF

6. Phone holder
   - The size of the phone holder is 12.7 x 171.1 mm. Make sure your device fits into the groove.

1.3.2 Back view



1. **HDMI port**. This port is for connection with an HDMI compatible device.
2. **DisplayPort**. This port is for connection with a DisplayPort compatible device.
3. **USB 3.2 Gen 1 Type-C (supports DP Alt mode).** This port is for connection with a DisplayPort/USB Type-C compatible device. This port is also for connection with a USB Type-C cable, which supports USB power delivery (depending on the signal source).


This monitor is Super-Speed USB 3.2 Gen 1 compatible (5Gbps). The port offer 7.5W power delivery with output voltage of 5V/1.5A.

4. **Earphone jack.** This port is only available when an HDMI/DisplayPort/USB Type-C cable is connected.
5. **AC-IN port.** This port connects the power cord.
6. **Kensington lock slot.**
7. **Control buttons.**

1.3.3 Other Function(s)

- Tripod socket atop

1/4-inch tripod socket on the monitor stand allows you to mount a camera, audio equipment or additional display.




- HDR

The monitor supports HDR format. When detecting HDR content, an "HDR ON" message will pop up.

- When displaying HDR content, the following function(s) are not available: **ELMB**, **ELMB SYNC**, **ELMB Setup**, **Sniper**, **GameVisual**, **Shadow Boost**, **Brightness**, **Contrast**, **Dynamic Dimming**, **Aspect Control**, **ASCR**, **Blue Light Filter**, **Display Color Space**, **Color Temp.**, **Saturation**, **Six-axis Saturation**, **Gamma**, **Power Setting**.
- When **Adjustable HDR** is enabled, the following function(s) can be adjusted: **Brightness, Contrast, Color Temp., Saturation, Six-axis Saturation**, **VividPixel**.

2.1 Assembling the monitor arm/base

1. Insert the base into the arm.
2. Fix the base to the arm by fastening the bundled screw.
3. Attach the arm into the monitor.




We recommend that you cover the table surface with soft cloth to prevent damage to the monitor.

Base screw size: M6 x 15 mm.

2.2 Cable management


You can organize the cables with the help of the cable management hole.

- **Arranging the cables**



2.3 Adjusting the monitor


- For optimal viewing, we recommend that you look at the full face of the monitor, then adjust the monitor to the angle that is most comfortable for you.
- Hold the stand to prevent the monitor from falling when you change its angle.
- The recommended adjusting angle is +20˚ to -5˚ (for tilt)/+45˚ to -45˚ (for swiveling/120 mm (for height adjustment)/±90˚ (for portrait view).



(Tilt) (Swivel) (Height adjustment)

Pivoting the monitor

1. Lift the monitor to the highest position.
2 Tilt the monitor to its maximum angle.
3. Pivot the monitor clockwise or counterclockwise to the angle you need.




It is normal that the monitor slightly shakes while you adjust the viewing angle.

2.4 Detaching the arm (for VESA wall mount)

The detachable arm of this monitor is specially designed for VESA wall mount.

To detach the arm:

1. Have the front of the monitor face down on a table.
2. Press the release button to detach the stand (arm and base) from the monitor.




We recommend that you cover the table surface with soft cloth to prevent damage to the monitor.

- The VESA wall mount kit (100 x 100 mm) is purchased separately.
- Use only the UL Listed Wall Mount Bracket with minimum weight/load 22.7kg (Screw size: M4 x 10 mm)

2.5 Connecting the cables

Connect the cables as the following instructions:



- **To connect the power cord**: Connect one end of the power cord securely to the monitor's AC input port, the other end to a power outlet.
- **To connect the HDMI/DisplayPort/USB Type-C cable:**
  a. Plug one end of the HDMI/DisplayPort/USB Type-C cable to the monitor's HDMI/DisplayPort/USB Type-C jack.
  b. Connect the other end of the HDMI/DisplayPort/USB Type-C cable to your device's HDMI/DisplayPort/USB Type-C jack.

When these cables are connected, you can choose the desired signal from the Input Select item in the OSD menu.

If you need to replace the power cord or the connection cable(s), please contact ASUS customer service.


- **To use the earphone:** connect the audio cable to the monitor's earphone jack.

2.6 Turning on the monitor

Press the power button ⏻ . See page 1-3 for the location of the power button. The power indicator ⏻ lights up in white to show that the monitor is ON.

3.1 OSD (On-Screen Display) menu

3.1.1 How to reconfigure



1. Press the ☰ (◎) button to activate the OSD menu.
2. Move the ☰ (◎) button up/down to navigate through the functions. Highlight the desired function and press the ☰ (◎) button to activate it. If the function selected has a sub-menu, move the ☰ (◎) button up/down again to navigate through the sub-menu functions. Highlight the desired sub-menu function and press the ☰ (◎) button or move the ☰ (◎) button right to activate it.
3. Move the ☰ (◎) button up/down to change the settings of the selected function.
4. To exit and save the OSD menu, press the ✕ button or move the ☰ (◎) left repeatedly until the OSD menu disappears. To adjust other functions, repeat steps 1-3.

3.1.2 OSD function introduction

1. Gaming



- **Overclocking**: The monitor can overclock to a maximum refresh rate of 380Hz.

Overclocking may cause screen flickering. To reduce such effects, disconnect the cable and use the monitor OSD to try again with a safer Max Refresh Rate.

- **Variable OD**: Improves the gray level response time of the LCD panel.
- **Variable Refresh Rate:** Allows an Variable Refresh Rate supported* graphics source to dynamically adjust display refresh rate based on typical content frame rates for power efficient, virtually stutter free and low-latency display update.

- This function is only available when the following settings are disabled: **ELMB**.
- ***Variable Refresh Rate** can only be activated within 48Hz~380Hz.
- *For supported GPUs, minimum PC system and driver requirements, please contact the GPU manufacturers.

- **ELMB Setup:**

* **ELMB: ELMB** can only be activated when **Variable Refresh Rate** is **OFF** and the refresh rate is higher than 100Hz. This function eliminates screen tearing, reduces ghosting and motion blur when playing games. The function includes 5-level clarity and position adjustment.

- When this function is enabled, the following function(s) are not available: **Variable Refresh Rate**, **ELMB SYNC**, **Brightness**, **Aspect Control**, **Dynamic Dimming**, **ASCR**, **Blue Light Filter**, **Variable OD**, **HDR Setting**.
- To activate **ELMB**, turn off **Variable Refresh Rate** first.

* **ELMB SYNC**: Allows you to turn on the function when **Variable Refresh Rate** is **ON**. This function eliminates screen tearing, reduces ghosting and motion blur when playing games.

When this function is enabled, the following function(s) are not available: **ELMB**, **Brightness**, **Aspect Control**, **Dynamic Dimming**, **ASCR**, **Blue Light Filter**, **HDR Setting**.

- **GamePlus**: The GamePlus function provides a toolkit and creates a better gaming environment for users when playing different types of games.
  - **FPS Counter**: The FPS (frames per second) counter lets you know how smooth the game is running.
  - **Crosshair**: The crosshair overlays with 6 different crosshair options letting you choose the one that best suits the game you're playing.
  - **Sniper**: This function is customized for first-person shooters. You can select the magnification ratio, the type of alignment in sequence and night vision mode.
  - **Timer**: You can position the timer on the upper left corner of the display so you can keep track of the gaming time.
  - **Stopwatch**: You can position the stopwatch on the upper left corner of the display so you can keep track of the gaming time.
  - **Display Alignment**: **Display Alignment** displays alignment lines on 4 sides of the screen, serving as an easy and handy tool for you to line up multiple monitors perfectly.
- **GameVisual**: The GameVisual function helps you select among different picture modes in a convenient way.
  - **Scenery Mode**: This is the best choice for scenery photo displaying with GameVisual™ Video intelligence Technology.
  - **Racing Mode**: This is the best choice for racing game playing with GameVisual™ Video intelligence Technology.
  - **Cinema Mode**: This is the best choice for movie watching with GameVisual™ Video intelligence Technology.
  - **RTS/RPG Mode**: This is the best choice for Real-Time Strategy (RTS)/ Role-Playing Game (RPG) playing with GameVisual™ Video intelligence Technology.
  - **FPS Mode**: This is the best choice for First Person Shooter game playing with GameVisual™ Video intelligence Technology.
  - **sRGB Mode**: This is the best choice for viewing photos and graphics from PCs.
  - **MOBA Mode**: This is the best choice for multiplayer online battle arena game playing with GameVisual™ Video intelligence Technology.
  - **Night Vision**: This is the best choice for dark scenery playing with GameVisual™ Video intelligence Technology.
  - **User Mode**: More items are adjustable in the Color menu.

- In the **MOBA Mode**, the following function(s) are not user-configurable: **Shadow Boost**, **VividPixel**, **Saturation**.
- In the **Night Vision**, the following function(s) are not user-configurable: **Saturation**.


- In the **sRGB Mode**, the following function(s) are not user-configurable: **Shadow Boost**, **Contrast**, **ASCR**, **Blue Light Filter, Display Color Space, Color Temp.**,**Saturation**, **Gamma**.

- **Shadow Boost**: Dark color enhancement adjusts monitor gamma curve to enrich the dark tones in an image, making dark scenes and objects much easier to be seen.

This function is only available in **Scenery Mode, Racing Mode, Cinema Mode, RTS/RPG Mode, FPS Mode, Night Vision, User Mode**.

- **ASUS DisplayWidget Center**: Displays a QR code for you to access the information about ASUS DisplayWidget Center.

2. Image



- **Brightness**: The adjusting range is from 0 to 100.
- **Contrast**: The adjusting range is from 0 to 100.
- **HDR Setting**: Contains 3 HDR modes, including **Gaming HDR**, **Cinema HDR** and **Console HDR**. When **Adjustable HDR** is enabled, the following functions can be adjusted: **Brightness, Contrast, Color Temp., Saturation, Six-axis Saturation, VividPixel**.

When displaying HDR content, the following function(s) are not available: **ELMB**, **ELMB SYNC**, **ELMB Setup**, **Sniper**, **GameVisual**, **Shadow Boost**, **Brightness**, **Contrast**, **Dynamic Dimming**, **Aspect Control**, **ASCR**, **Blue Light Filter**, **Display Color Space**, **Color Temp.**, **Saturation**, **Six-axis Saturation**, **Gamma**, **Power Setting**, **VividPixel**.

- **Dynamic Dimming**: Synchronizes with contents while contrast changing to execute backlight dynamic dimming.

When this function is enabled, the following function(s) are disabled: **ELMB**, **ELMB SYNC**, **Blue Light Filter**, **ASCR**, **Aspect Control**.

- **ASCR**: Turns on/off the ASCR (ASUS Smart Contrast Ratio) function.

This function is only available when the following setting(s) are disabled: **ELMB**, **ELMB SYNC**, **Dynamic Dimming**.

- **Aspect Control**: Adjust the aspect ratio to **16:9** or **Square** to enjoy different gaming scenario.
  - **16:9**: Simply choose **Fill Up** or **24.5" Simulation** under **Full** for better FPS gaming size; or you can choose **Pixel by Pixel** under Windows Display setting.
  - **Square**: Provides multiple square aspect ratio choices with different screen sizes, including **Full**, **Equivalent** and **Pixel by Pixel**.

This function is only available when the following setting(s) are disabled: **ELMB**, **ELMB SYNC**, **Dynamic Dimming**.

- **Blue Light Filter**:
  - **OFF**: No change.
  - **Level 1~Level 4**: The higher the level, the less blue light is scattered. When **Blue Light Filter** is activated, the default settings of **Racing Mode** will be automatically imported. From **Level 1** to **Level 4**, the Brightness function is user-configurable.


When this function is enabled, the following function(s) will be disabled: **ELMB**, **ELMB SYNC**, **Dynamic Dimming**.

The monitor uses low blue light panel and compliance with TÜV Rheinland Low Blue Light Hardware Solution at factory reset/default setting mode (Brightness: 65%, Contrast: 80%, CCT: 6500K, Preset mode: Racing Mode, Power Setting: YES).

- Please refer to the following to alleviate eye strains:
- Users should take some time away from the display if working for long hours. It is advised to take short breaks (at least 5 mins) after around 1 hour of continuous working at the computer. Taking short and frequent breaks is more effective than a single longer break.
- To minimize eye strain and dryness in your eyes, you should rest the eye periodically by focusing on objects that are far away.
- Eye exercises can help to reduce eye strain. Repeat these exercises often. If eye strain continues, please consult a physician. Eye exercises: (1) Repeating look up and down (2) Slowly roll your eyes (3) Move your eyes diagonally.
- High energy blue light may lead to eye strain and AMD (Age-Related Macular Degeneration). Blue light Filter reduces 70% (max.) of harmful blue light to avoid CVS (Computer Vision Syndrome).

- **VividPixel**: This function enhances the outline of the displayed picture and generates high-quality images on screen.

3. Color



- **Display Color Space**: Selects the color space for the monitor color output.
- **Color Temp.**: Contains 8 modes including **4000K, 5000K, 6500K, 7500K , 8200K, 9300K, 10000K** and **User**.
- **Saturation**: The adjusting range is from 0 to 100.
- **Six-axis Saturation**: Adjusts the saturation for R, G, B, C, M, Y.
- **Gamma**: Allows you to set the color mode to **1.8, 2.0, 2.2, 2.4** or **2.6**.


4. Input Select

In this function, you can select your desired input source.



- **Auto Input Detection**: When enabled, the system will automatically select the latest inserted I/O port.
- **USB-C/DisplayPort/HDMI**: Manually selects the input source.

5. MyFavorite




- **Shortcut**:
  - **Shortcut 1**/**Shortcut 2**: Sets the shortcut functions for shortcut buttons.

When a certain function is selected or activated, your shortcut button may not support. Available function choices: **GamePlus**, **GameVisual**, **Variable OD**, **Brightness**, **Mute**, **Shadow Boost**, **Contrast**, **Input Select**, **HDR Setting**, **Blue Light Filter**, **Color Temp.**, **Volume (Earphone Out)**, **Customized Setting-1**, **Customized Setting-2**.

- **Customized Setting**:
  - **Setting 1**/**Setting 2**: Loads/Saves all settings on the monitor.

6. System Setup



- **Language**: There are 23 languages for your selection, including English, French, German, Italian, Spanish, Dutch, Portuguese, Russian, Czech, Croatian, Polish, Romanian, Hungarian, Turkish, Simplified Chinese, Traditional Chinese, Japanese, Korean, Thai, Indonesian, Persian, Ukrainian, Vietnamese.
- **Sound**: Sets the sound related settings from this menu.
  - **Volume (Earphone Out)**: The adjusting range is from 0 to 100.
  - **Mute**: Toggles the monitor sound between on and off.
- **Power Indicator:** Turns the power LED indicator on/off.
- **Power Key Lock:** Enables or disables the power key.

- **Key Lock**: To disable all function keys. Move and hold the ✣ (5-way) button downward for over 5 seconds to cancel the key lock function.
- **Power Setting:**
  - **Performance Mode**: Performance mode setting may result in higher power consumption.
  - **Power Saving Mode**: Power saving mode may cause limited luminance performance.
- **OSD Setup**:
  - Adjusts the OSD position.
  - Adjusts the OSD timeout from 10 to 120 seconds.
  - Adjusts the OSD background from opaque to transparent.
  - Enables or disables the DDC/CI function.
- **DisplayPort Stream**: Compatibility with graphic card. Select **DisplayPort 1.2**, **DisplayPort 1.4** by graphic card DP version.
- **ASUS Power Sync**: Allow the power on/off control of the console device or setup box, such as Apple TV, Sony PlayStation, Xbox Series X/S, Nintendo Switch through the monitor. The default setting is **ON**. If the monitor is turned on, the CEC source device will automatically power on, and vice versa. If the CEC source device is turned on, the monitor will automatically power on.
- **Information**: Shows the monitor information.
- **All Reset**: Selecting **Yes** allows you to restore the default settings.

3.2 Specifications summary


Panel type	TFT LCD
Panel size	27"W (68.5 cm) wide screen
Max. resolution	1920 x 1080
Pixel pitch	0.3108 mm x 0.3108 mm
Brightness (Typ.)	400 cd/m²
Contrast ratio (Typ.)	1000:1
Viewing angle(H/V) CR>10	178˚/178˚
Display colors	16.7 M
Response time	0.3 ms (GTG, min.); 1 ms (GTG)
Color temperature selection	8 color temperatures
Analog input	No
Digital input	DisplayPort v1.4 x 1, HDMI v2.1 x 1, USB Type-C x 1
Earphone jack	Yes
Audio input	No
Speaker (Built-in)	No
USB 3.2 Gen 1 port	No
Colors	Gray
Power LED	White (On)/Amber (Standby)
Tilt	+20˚~ -5˚
Pivot	+/-90˚
Swivel	+45˚~ -45˚
Height adjustment	120 mm
VESA wall mount	100 x 100 mm
Kensington lock	Yes
Voltage rating	AC: 100~240V
Power consumption	Power On: < 20 W**, Standby: < 0.5 W, Power Off: < 0.3 W
Temperature (Operating)	0˚C~40˚C
Temperature (Non-operating)	-20˚C~+60˚C
Dimensions (W x H x D)	614.15 x 366.71 x 65.80 mm (without stand) 614.15 x 218.83 x 510.32 mm (with stand, lowest) 614.15 x 218.83 x 394.95 mm (with stand, highest) 828 x 176 x 476 mm (package)
Weight (Esti.)	3.9 kg (without stand); 6.5 kg (Net); 9.0 kg (Gross)
Multi-languages	23 languages (English, French, German, Italian, Spanish, Dutch, Portuguese, Russian, Czech, Croatian, Polish, Romanian, Hungarian, Turkish, Simplified Chinese, Traditional Chinese, Japanese, Korean, Thai, Indonesian, Persian, Ukrainian, Vietnamese)

Accessories	Quick start guide, warranty card, power cord, DisplayPort cable (optional), HDMI cable (optional), USB Type-C cable (optional), ROG sticker, ROG pouch
Compliance and standards	cTUVus, FCC, IECS(B), CB, CE, ErP, WEEE, EU Energy Label, UkrSEPRO, Ukarine Energy, CU, CCC, CEL, BSMI, RCM, MEPS, VCCI, PSE, J-MOSS, KCC, Korea MEPS, Vietnam MEPS, CEC, TUV flicker free, TUV low blue light, Windows 10/11 WHQL, EAEU RoHs, KC, PC Recycle, PSB.

***Specifications are subject to change without notice.**

****Measuring a screen brightness of 200 nits without audio/USB/Card reader connection.**

3.3 Outline dimensions



3.4 Troubleshooting (FAQ)

Problem	Possible Solution
Power LED is not ON	• Press the ⏻ button to check if the monitor is in the ON mode. • Check if the power cord is properly connected to the monitor and the power outlet.
The power LED lights white and there is no screen image	• Check if the monitor and the computer are in the ON mode. • Make sure the signal cable is properly connected the monitor and the computer. • Inspect the signal cable and make sure none of the pins are bent. • Connect the computer with another available monitor to check if the computer is properly working.
Screen image is too light or dark	• Adjust the Contrast and Brightness settings via OSD.
Screen image bounces or a wave pattern is present in the image	• Make sure the signal cable is properly connected to the monitor and the computer. • Move electrical devices that may cause electrical interference.
Screen image has color defects (white does not look white)	• Inspect the signal cable and make sure that none of the pins are bent. • Perform All Reset via OSD. • Adjust the R/G/B color settings or select the Color Temperature via OSD.
Brightness decreases after displaying HDR content for a period of time	• Turn off the monitor by pressing the power button and then turn on the monitor. • Turn off the monitor by disconnecting the power cord and then turn on the monitor. • Reactivate the HDR function on your device.

3.5 Supported operating mode

Native timings

Resolution Frequency	HDMI Refresh rate	DisplayPort/USB Type-C Refresh rate
640 x 480	60Hz	60Hz
640 x 480	75Hz	75Hz
800 x 600	60Hz	60Hz
800 x 600	75Hz	75Hz
1024 x 768	60Hz	60Hz
1024 x 768	75Hz	75Hz
1280 x 960	60Hz	60Hz
1280 x 1024	60Hz	60Hz
1280 x 720	60Hz	60Hz
1600 x 900	60Hz	60Hz
1920 x 1080	60Hz	60Hz
1920 x 1080	144Hz	144Hz
1920 x 1080	240Hz	240Hz
1920 x 1080	280Hz	280Hz
1920 x 1080	360Hz	360Hz
1920 x 1080	-	380Hz

For Square timings

Resolution Frequency	HDMI Refresh rate	DisplayPort/USB Type-C Refresh rate
640 x 480	60Hz	60Hz
640 x 480	75Hz	75Hz
800 x 600	60Hz	60Hz
800 x 600	75Hz	75Hz
1024 x 768	60Hz	60Hz
1024 x 768	75Hz	75Hz
1280 x 960	60Hz	60Hz
1280 x 1024	60Hz	60Hz
1280 x 720	60Hz	60Hz
1600 x 900	60Hz	60Hz
1280 x 960	360Hz	360Hz
1024 x 768	360Hz	360Hz
1152 x 864	360Hz	360Hz
1728 x 1080	360Hz	360Hz
1440 x 1080	360Hz	360Hz
1280 x 960	-	380Hz
1024 x 768	-	380Hz
1152 x 864	-	380Hz
1728 x 1080	-	380Hz
1440 x 1080	-	380Hz

For 16:9 (24.5" Simulation) aspect control timings

Resolution Frequency	HDMI Refresh rate	DisplayPort/USB Type-C Refresh rate
640 x 480	60Hz	60Hz
640 x 480	75Hz	75Hz
800 x 600	60Hz	60Hz
800 x 600	75Hz	75Hz
1024 x 768	60Hz	60Hz
1024 x 768	75Hz	75Hz
1280 x 960	60Hz	60Hz
1280 x 1024	60Hz	60Hz
1280 x 720	60Hz	60Hz
1600 x 900	60Hz	60Hz
1920 x 1080	60Hz	60Hz
1920 x 1080	360Hz	360Hz
1744 x 982	60Hz	60Hz
1744 x 982	120Hz	120Hz
1744 x 982	360Hz	360Hz
1744 x 982	-	380Hz

Video Timing

Resolution Frequency	Refresh Rate
640 x 480p	59.94Hz/60Hz
720 x 480p 16:9	59.94Hz/60Hz
720 x 480p 4:3	59.94Hz/60Hz
720 x 576p 16:9	50Hz
720 x 576p 4:3	50Hz
1280 x 720p	50Hz
1280 x 720p	59.94Hz/60Hz
1920 x 1080p	23.98Hz/24Hz
1920 x 1080p	25Hz
1920 x 1080p	29.97Hz/30Hz
1920 x 1080p	50Hz
1920 x 1080p	59.94Hz/60Hz
1920 x 1080p	119.88Hz/120Hz
1920 x 1080p	100Hz


REPUBLIC OF
GAMERS