DDR4 2400 Qualified Vendors List (QVL)								
Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	et suppor 1 DIMM
ADATA	AD4S240038G17-B	8GB	DS	-	-	-	1.2	•
ADATA	AD4S2400W8G17-B	8GB	DS	-	H5AN4G8NAFRUHC	-	1.2	•
ADATA	AD4S400W4G17-B	4GB	DS	-	-	-	1.2	•
crucial	CT16G4SFD824A.16FB1	16GB	DS	-	-	-	1.2	•
crucial	CT8G4SFS824A.8FB1	8GB	DS	-	-	-	1.2	•
Kingston	HX426LS15IBK2/8	4GB	DS	-	H5AN4G8NMFRTFC	-	-	•
panram	W4N2400PS-8G	8GB	DS	-	DTCCHA76DG1	-	1.2	٠
Team	TED416G2400C16-SBK	16GB	DS	-	T4D10248HT-21	-	1.2	•
Team	TED44G2400C16-SBK	4GB	DS	-	T4D5128HT-24	-	1.2	•
Team	TED48G2400C16-SBK	8GB	DS	-	T4D10248HT-24	-	1.2	•
Transcend	TS512MSH64V4H-I	2GB	SS	-	0	-	1.2	٠

2 DIMM Slots

• **1 DIMM**: Supports one module inserted in any slot as Single-channel memory configuration

• **2 DIMM**: Supports 2 modules inserted into both the blue or black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-

-Memory module with memory frequency higher than 2133 MHz and its corresponding timing or the loaded XMP Profile is not the JEDEC memory standard. The stability and compatibility of these memory modules depend on the CPU's capabilities and other installed devices. -Always install DIMMs with the same CAS latency. For optimal compatibility, we recommend that you install memory modules of the same version or date code (D/C) from the same vendor. Check with the retailer to get the correct memory modules.