

DDR3 1333 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMV8GX3M1A1333C9	8GB	DS	CORSAIR	512M8DCJGELA0401213	-	-	•	•
TEAM	TED34GM1333C9BK	4GB	DS	HYNIX	DWLDL9J5HL	9-9-9-24	1.5V	•	•
TEAM	TED38GM1333C9BK	8GB	DS	HYNIX	DT38J3bbDHJ	9-9-9-24	1.5V	•	•

DDR3 1600 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
KINGSTON	KHX1600C9D3/4G	4GB	DS	-	-	-	1.65V	•	•
CORSAIR	CMV4GX3M1A1600C11	4GB	SS	CORSAIR	512M8DDLGPSSBO381320	-	-	•	•
CORSAIR	CMY8GX3M2A1600C9	4GB	SS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CML8GX3M2A1600C9	4GB	DS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CMZ4GX3M1A1600C9	4GB	DS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CMZ8GX3M2A1600C9	4GB	DS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CML16GX3M2A1600C10	8GB	DS	-	-	10-10-10-27	1.50V	•	•
CORSAIR	CMY16GX3M2A1600C9	8GB	DS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CMY32GX3M4A1600C9	8GB	DS	-	-	9-9-9-24	1.50V	•	•
CORSAIR	CMZ8GX3M1A1600C10(XMP)	8GB	DS	-	-	10-10-10-27	1.50V	•	•
KINGSTON	KVR16N11S8/4(Low Profile)	4GB	SS	KINGSTON	U317X8BRRA19	-	1.50V	•	•
SANMAX	SMD-4G28N1P-16KM	4GB	SS	ELPIDA	J4208BBBG-GN-F	-	-	•	•
SANMAX	SMD-8G28NP-16KM	8GB	DS	ELPIDA	J4208BBBG-GN-F	-	1.50V	•	•
TEAM	TLD34G1600HCBK	4GB	SS	-	-	9-9-9-24	1.5V	•	•
TEAM	TED34GM1600C11BK	4GB	DS	HYNIX	DW3DJJ273	-	1.5V	•	•
TEAM	TED38GM1600C11BK	8GB	DS	HYNIX	DT38J3bb4AM	11-11-11-28	1.5V	•	•
TEAM	TLD38G1600HC9BK	8GB	DS	-	-	9-9-9-24	1.5V	•	•

DDR3 1866 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMY16GX3M2A1866C9(Ver3.24)	8GB	DS	-	-	9-10-9-27	1.50V	•	•
CORSAIR	CMY8GX3M2A1866C9	4GB	SS	-	-	9-10-9-27	1.50V	•	•
CORSAIR	CMY32GX3M4A1866C9	8GB	DS	-	-	9-10-9-27	1.50V	•	•
CORSAIR	CMZ16GX3M2A1866C10(Ver4.21)	8GB	DS	-	-	10-11-10-30	1.50V	•	•
AMD	AP38G1869J2K	8GB(4GBx2)	DS	-	-	9-10-9-27	1.5V	•	•
TEAM	TED34GM1866C13BK	4GB	DS	HYNIX	DW3DJ472B3	-	1.5V	•	•
TEAM	TLD34G1866HC9KBK	4GB	DS	-	-	9-11-9-27	1.5V	•	•
TEAM	TLD38G1866HC10SBK	8GB	DS	-	-	10-11-10-30	1.5V	•	•

DDR3 2133 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMY8GX3M2A2133C11R	8GB(4 x	SS	-	-	11-11-11-27	1.50V	•	•
CORSAIR	CMD8GX3M2B2133C9(Ver5.12)	4GB	DS	-	-	9-11-11-31	1.65V	•	•
CORSAIR	CMD16GX3M2A2133C9(Ver4.21)	8GB	DS	-	-	9-11-11-31	1.65V	•	•
CORSAIR	CMZ8GX3M2A2133C11(Ver4.21)	4GB	SS	-	-	11-11-11-27	1.50V	•	•
CORSAIR	CMD32GX3M4A2133C9(Ver4.21)	8GB	DS	-	-	9-11-11-31	1.65V	•	•
AMD	AG34G2130UI	4GB	SS	-	-	10-11-11-30	1.65V	•	•
AMD	AP38G2133U2K	4GB	DS	-	-	11-12-11-30	1.65V	•	•
TEAM	TLD34G2133HC11ABK	4GB	SS	-	-	11-11-11-31	1.65V	•	•
TEAM	TLD38G2133HC11ABK	8GB	DS	-	-	11-13-13-31	1.65V	•	•

DDR3 2400 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMD32GX3M4A2400C10(Ver5.29)	8GB	DS	-	-	10-12-12-31	1.65V	•	•
CORSAIR	CMY16GX3M2A2400C10R(Ver4.21)	8GB	DS	-	-	10-12-12-31	1.65V	•	•
TEAM	TXD38G2400HC10QBK	8GB	DS	-	-	10-12-12-31	1.62V	•	•

DDR3 2666 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
CORSAIR	CMD16GX3M4A2666C10 (Ver4.13)	4GB	DS	-	-	10-12-12-31	1.65V	•	•

DDR3 2933 Qualified Vendors List (OVL)

Vendors	Part No.	Size	SS/DS	Chip Brand	Chip NO.	Timing	Voltage	DIMM socket support (Optional)	
								1 DIMM	2 DIMM
G.SKILL	F3-2933C12D-16GTDXG	8GB	DS	-	-	12-14-14-35	1.65V	•	•
G.SKILL	F3-2933C12Q-16GTDXG	4GB	SS	-	-	12-14-14-35	1.65V	•	•

4 DIMM Slots

- **1 DIMM:** Supports one module inserted in any slot as Single-channel memory configuration
- **2 DIMM:** Supports 2 modules inserted into both the **blue** or **black** slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is -It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.