TUF GAMING Z590-PLUS WIFI_One Page Spec		
Note: The specifications are subject to change without notice.		
СРИ	Intel® Socket LGA1200 for 11 th Gen Intel® Core™ processors & 10 th Gen Intel® Core™, Pentium® Gold and Celeron® Processors	
	Supports Intel® 14 nm CPU	
	Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0**	
	* Refer to www.asus.com for CPU support list.	
	** Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.	
Chipset	Intel® Z590 Chipset	
	4 x DIMM, Max. 128GB, DDR4 5133(OC)/5000(OC)/4800(OC)/4700(OC)/4600(OC)/4500(OC)/4400(OC) /4266(OC)/4133(OC)/4000(OC)/3866(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333(OC)/3200/3000/2933/2800 /2666/2400/2133 MHz Non-ECC, Un-buffered Memory*	
	Dual Channel Memory Architecture	
	Supports Intel® Extreme Memory Profile (XMP)	
Memory	OptiMem II	
	* 10 th Gen Intel® Core™ i7/i9 processors support 2933/2800/2666/2400/2133 natively, others will run at the maximum transfer rate of DDR4 2666MHz.	
	* 11th Gen Intel® processors support 3200/2933/2800/2666/2400/2133 natively.	
	* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists), and memory frequency support depends on the CPU types.	
Graphics	1 x DisplayPort 1.4**	
	1 x HDMI™ 2.0***	
	* Graphics specifications may vary between CPU types.	
	** Intel® 11 th & 10 th processors support DisplayPort 1.4 with max. resolution of 4096 x 2304 @60Hz. Please refer to www.intel.com for any updates.	
	*** Only Intel® 11 th processors, support HDMI™ 2.0 with max. resolution of 4K@60Hz, others would only support HDMI™ 1.4 with max. resolution of 4K@30Hz .Please refer to www.intel.com for any update.	
	**** VGA resolution support depends on processors' or graphic cards' resolution.	
Expansion Slots	Intel® 11th & 10th Gen Processors	
	1 x PCle 4.0/3.0 x16 slot*	
	- Intel® 11 th processors support PCIe 4.0 x16	
	- Intel® 10 th processors support PCIe 3.0 x16	
	Intel® Z590 Chipset	
	1 x PCle 3.0 x16 slot (supports x4 mode)	
	2 x PCle 3.0 x1 slots	
	* Enable RST PCIe Storage Remapping for PCH attached PCIe slots to activate Intel® Optane Memory.	
Storage	Total supports 3 x M.2 slots and 6 x SATA 6Gb/s ports	
	Intel® 11th Gen Processors	
	M.2_1 slot (Key M), type 2242/2260/2280/22110	
	- Only Intel® 11 th processors support PCIe 4.0 x4 mode, this slot will be disabled for other CPUs	

	Intel® Z590 Chipset
	M.2_2 slot (Key M), type 2242/2260/2280/22110 (supports PCle 3.0 x4 & SATA modes)***
	M.2_3 slot (Key M), type 2242/2260/2280 (supports PCle 3.0 x4 & SATA modes)****
	6 x SATA 6Gb/s ports
Storage	* Raid function for PCIe mode SSD in Intel® Rapid Storage Technology is available with either 1. Intel® SSDs installed in both CPU-attached and PCH-attached slots, or 2. any other 3rd party SSDs installed in PCH-attached
	slots.
	** To enable Intel® Optane™ Memory (Hybrid Storage device), it must be installed in PCH-attached slots with
	Intel® Rapid Storage Technology. *** M.2_2 shares bandwidth with SATA6G_2. When M.2_2 runs SATA mode, SATA6G_2 will be disabled.
	**** M.2_3 shares bandwidth with SATA6G_56. When M.2_3 is occupied, SATA6G_56 will be disabled.
	1 x Intel® 1225-V 2.5Gb Ethernet
Ethernet	TUF LANGuard
	Intel® Wi-Fi 6
Wireless &	2x2 Wi-Fi 6 (802.11 a/b/g/n/ac/ax)
Bluetooth	Supports 2.4/5GHz frequency band Bluetooth v5.0 or later
	Rear USB (Total 7 ports)
	1 x USB 3.2 Gen 2x2 port (1 x USB Type-C®)
	2 x USB 3.2 Gen 2 ports (2 x Type-A)
	2 x USB 3.2 Gen 1 ports (2 x Type-A)
USB	2 x USB 2.0 ports (2 x Type-A)
	Front USB (Total 7 ports)
	1 x USB 3.2 Gen 1 connector (suppports USB Type-C®)
	1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports
	2 x USB 2.0 headers support additional 4 USB 2.0 ports
	Realtek ALC S1200A 7.1 Surround Sound High Definition Audio CODEC*
	- Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking - Supports up to 24-Bit/192 kHz playback
	Audio Features
Audio	- Audio Shielding
	- Rear optical S/PDIF out port
	- Premium Japanese audio capacitors
	- Dedicated audio PCB layers
	- Audio cover
	1 x USB 3.2 Gen 2x2 port (1 x USB Type-C®)
Back Panel I/O Ports	2 x USB 3.2 Gen 2 ports (2 x Type-A)
	2 x USB 3.2 Gen 1 ports (2 x Type-A)
	2 x USB 2.0 ports (2 x Type-A)
	1 x DisplayPort
	1 x HDMI™ port
	1 x ASUS Wi-Fi Module
	1 x Intel® I225-V 2.5Gb Ethernet port
	5 x Audio jacks
	1 x Optical S/PDIF out port
	1 x PS/2 Keyboard/Mouse combo port

Fan and Cooling related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 1 x 4-pin AIO Pump header 3 x 4-pin Chassis Fan headers Power related 1 x 24-pin Main Power connector 1 x 8-pin +12V Power connector 1 x 4-pin +12V Power connector Storage related 3 x M.2 slots (Key M) 6 x SATA 6Gb/s ports Internal I/O Connectors USB 1 x USB 3.2 Gen 1 connector (supports USB Type-C[®]) 1 x USB 3.2 Gen 1 headers supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports Miscellaneous 2 x AURA Addressable Gen 2 headers 2 x AURA RGB headers 1 x Clear CMOS header 1 x COM Port header 1 x Front Panel Audio header (AAFP) 1 x 20-3 pin System Panel header with Chassis intrude function 1 x Thunderbolt™ header **ASUS TUF PROTECTION** - DIGI+ VRM (- Digital power design with DrMOS) - Enhanced DRAM Overcurrent Protection - TUF LANGuard - Overvoltage Protection **ASUS Q-Design** - M.2 Q-Latch - Q-DIMM - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]) - Q-Slot Special **Features ASUS Thermal Solution** - M.2 heatsink - VRM heatsink design **ASUS EZ DIY** - ProCool - Pre-mounted I/O shield - SafeSlot **AURA Sync** - AURA RGB headers

Addressable Gen 2 RGB headers

	ASUS Exclusive Software
	Armoury Crate
	- AURA Creator
	- AURA Sync
	- Two-Way Al Noise Cancelation
	Al Suite 3
	- Performance And Power Saving Utility
	TurboV EVO
	EPU EPU
	Digi+ VRM
	Fan Xpert 4
	- EZ update
Software	TUF GAMING CPU-Z
Features	Al Charger
	ASUS Turbo LAN
	DAEMON Tools
	DTS Custom for GAMING Headsets
	MyASUS
	Norton Anti-virus software (Free Trial version)
	WinRAR
	UEFI BIOS
	ASUS EZ DIY
	- ASUS CrashFree BIOS 3
	- ASUS EZ Flash 3
	- ASUS UEFI BIOS EZ Mode
BIOS	192 (128+64) Mb Flash ROM, UEFI AMI BIOS
	WOL by PME, PXE
	Cables
	2 x SATA 6Gb/s cables
	Miscellaneous
	1 x ASUS Wi-Fi moving antennas
	2 x M.2 Rubber Packages
	1 x M.2 SSD screw package
Accessories	1 x TUF Gaming sticker
	Installation Media
	1 x Support DVD
	Documentation
	1 x TUF Certification card
	1 x User manual
Operating System	Windows® 10 64-bit
Form Factor	ATX Form Factor
	12 inch x 9.6 inch (30.5 cm x 24.4 cm)