

Pro WS C422-ACE

ECC RDIMM DDR4 2133 Qualified Vendors List (QVL)

Vendors	Part No.	Size	Timing	Voltage	DIMM socket support (Optional)		
					2 DIMM	4 DIMM	8 DIMM
SAMSUNG	M386A8K40BM1-CPB	64GB	15-15-15-36	1.2	•	•	•

ECC RDIMM DDR4 2933 Qualified Vendors List (QVL)

Vendors	Part No.	Size	Timing	Voltage	DIMM socket support (Optional)		
					2 DIMM	4 DIMM	8 DIMM
Kingston	KSM29RS8/8MEI	8GB	21-21-21	1.2	•	•	•
Kingston	KSM29RS4/16MEI	16GB	21-21-21	1.2	•	•	•
Kingston	KSM29RS4/32MEI	32GB	21-21-21	1.2	•	•	•

8-DIMM

- **4 DIMM:** Supports 4 modules inserted into both the A1, B1, C1, and D1 slots as one set of DIMMs operating in a quad-channel memory configuration
- **8 DIMM:** Supports 8 modules inserted into all slots as two sets DIMMs operating in a quad-channel memory configuration

- Please ensure all memory modules are from a single validated kit. Do not combine DIMMs from multiple kits—even if they are the same make and model. Mixing and matching DIMMs can result in failure to boot and compatibility cannot be guaranteed.

- At default UEFI settings, the memory operating frequency depends on the Serial Presence Detect (SPD) profile the kit is programmed with, which is the standard way of accessing information from a module.