

# RS501A-E12-RS12U

## AMD Single-socket, 1U Rack Server



1U



1



24

### 5th Generation AMD EPYC Processors

ASUS RS501A-E12-RS12U was designed for general purpose application. With the front 12 hot-swap bays and optional internal 4 bays, RS501A-E12-RS12U is the economic design for rack placement.

### FEATURE

- 1 x AMD EPYC 9005 series processor
- With 24\*DDR5 DIMM up to 5200Mhz
- 2 x M.2 socket support
- 3 x PCIe + 1 x OCP expansion in 1U rack sever.
- Internal 4-bay cage for mid-bay SKU

### AMD EPYC™ 9005 series processors support

RS501A-E12 series is built on the AMD platform to deliver incredible performance and offer more CPU cores powered by AMD EPYC 9005 series processors.

### Industry-leading memory capability

With 2 DIMM per channel design, RS501A-E12 Series supports up to 24 x DIMM slots. The CPU's memory controller supports DDR5 memory with 12 channels up to 5200Mhz . We deliver the industry-leading technology of server memory for our customers' business.

### Amazing compact design of internal 4-bay cage option for more storage possibility

ASUS RS501A-E12-RS12U features an internal 4-bay cage option\*. We redefine the possibility of 1U rack from traditional image of Max. 12 storage bays to the whole new image of 16 drives support.

### Comprehensive IT infrastructure management solution

ASUS RS501A-E12-RS12U server features an embedded ASMB11-iKVM (BMC, AST2600) and is bundled with ASUS Control Center to provide comprehensive out-of-band and in-band management capability.

### Target market

- General-purpose Rack Server
- Enterprise Application

1. 12 x 2.5" Hot-swap Storage Bays
2. Internal 4-bay cage for mid-bay SKU only\*
3. 1 x PCIe Gen5 x16 slot for full-height, half-length card
4. 1 x PCIe Gen5 x16 slot for low-profile card
5. 1 x PCIe Gen5 x16 slot for low-profile card
6. 1 x OCP 3.0 Mezzanine socket
7. 1+1 Platinum/ Titanium CRPS
8. AMD EPYC™ 9005 Processor Family (Up to 360W)
9. 24\*DDR5 DIMM up to 5200Mhz

\* Internal Storage Bays cannot be purchased separately



## RS501A-E12-RS12U

## SPECIFICATION

<b>Processor</b>		1 x Socket SP5 (LGA 6096) Supports AMD EPYC™ 9005 series processors or AMD EPYC™ 9004 series processors, up to 360W*
<b>Memory</b>	<b>Total Slots</b>	<b>24</b> 12-channel, 2 DIMM per channel
	<b>Capacity</b>	Up to 2,304GB
	<b>Memory Type</b>	<div> <div>AMD EPYC™ 9005 series processors</div> <div>DDR5 6400/5600 RDIMM/3DS RDIMM</div> <div>2DPC (1 of 2) up to 5200 with "6400 RDIMM", other 4800</div> <div>2DPC (2 of 2, 1R+1R ) up to 4400, with "6400 RDIMM", other 4000</div> <div>2DPC (2 of 2, 2R+2R ) up to 4000, with "6400 RDIMM", other 3600</div> </div> <div> <div>AMD EPYC™ 9004 series processors</div> <div>DDR5 4800 RDIMM/ 3DS RDIMM</div> <div>2DPC (1 of 2) up to 4800,</div> <div>2DPC (2 of 2, 1R+1R ) up to 4000</div> <div>2DPC (2 of 2, 2R+2R ) up to 3600</div> </div>
	<b>Memory Size</b>	96GB, 64GB, 32GB, 16GB (RDIMM) *Refer to ASUS server AVL for the latest update
<b>Expansion Slots</b>	<b>Total Slots</b>	3 PCIe Gen5 slots + 1 OCP3.0
	<b>Slot Type</b>	1 x PCIe x16 slot (Gen5 x16 link, FH, HL) 1 x PCIe x16 slot (Gen5 x16 link, LP, HL) 1 x PCIe x16 slot (Gen5 x8 link, LP, HL) 1 x OCP3.0 socket (Gen5 x16 link)
<b>Storage Bays</b>		Front: 12 x 2.5" Hot-swap Storage Bays (12 x SATA/SAS/ U.2 or U.3 NVMe Devices) Mid-bays SKU support up to 16NVMe/SATA  2 x M.2 socket (Gen4 x4 link or SATA mode, up to 22110 module)
<b>Networking</b>	<b>LAN</b>	1 x Dual Port Intel I350-AM2 Gigabit LAN controller 1 x Dedicated Management port (BMC AST2600)
<b>Security</b>		Optional TPM module PFR module (support by project)
<b>Rear I/O Ports</b>		2 x USB 3.2 Gen1 ports 2 x Gigabit LAN ports (RJ45) 1 x Management port (RJ45) 1 x VGA port
<b>Switch/LED</b>		Front: 1 x Power Button/LED 1 x Location Button/LED 1 x Message LED 2 x LAN LED  Rear: 1 x Port80 LED (Q-Code) 1 x Power Switch w/ LED 1 x Location Switch w/ LED 1 x Message LED
<b>OS Support</b>	*Please find the latest OS support from <a href="https://www.asus.com/event/Server/OS_support_list/OS.html">https://www.asus.com/event/Server/OS_support_list/OS.html</a>	
<b>Management Solution</b>	<b>Software</b>	ASUS Control Center (in-band)
	<b>Out of Band Remote Management</b>	ASMB11-iKVM (BMC AST2600)
<b>Dimension</b>		842.5mm x 449mm x 43.85mm (1U) 33.17" x 17.68" x 1.73"
<b>Net Weight Kg (CPU, DRAM &amp; HDD not included)</b>		14.16 kg
<b>Gross Weight Kg (CPU, DRAM &amp; HDD not included, Packing include)</b>		19.16 kg
<b>Power Supply (following different configuration by region)</b>		1+1 Redundant 1200W Platinum Power Supply 1+1 Redundant 1600W 80 PLUS Titanium Power Supply
<b>Environment</b>		Operation temperature: 10°C ~ 35°C Non operation temperature: -40°C ~ 70°C Non operation humidity: 20% ~ 90% ( Non condensing)

\*CPU with TDP supported under specific conditions. For higher wattage CPU demand, please contact us

## RS501A-E12 Series

## SPECIFICATION

Series	RS501A-E12 Series Support Matrix		
Model	RS501A-E12-RS12U	RS501A-E12-RS4	RS501A-E12-RS4U
Processor	1 x Turin CPU or 1 x Genoa CPU		
GPU	Up to 2 single-slot GPU cards		
Memory	<p>24 x DIMM slots</p> <p>with AMD EPYC™ 9005 series processors DDR5 6400/5600 RDIMM/3DS RDIMM Maximum 2,304GB 2DPC (1 of 2) up to 5200 with "6400 RDIMM", other 4800 2DPC (2 of 2, 1R+1R ) up to 4400, with "6400 RDIMM", other 4000 2DPC (2 of 2, 2R+2R ) up to 4000, with "6400 RDIMM", other 3600</p> <p>with AMD EPYC™ 9004 series processors DDR5 4800 RDIMM/ 3DS RDIMM Maximum 2,304GB 2DPC (1 of 2) up to 4800, 2DPC (2 of 2, 1R+1R ) up to 4000 2DPC (2 of 2, 2R+2R ) up to 3600</p>		
M.2	2 x PCIe x4 or 2 x SATA		
Expansion	<p>1 x PCIe x16 slot (Gen5 x16 link, FH, HL)</p> <p>1 x PCIe x16 slot (Gen5 x16 link, LP, HL)</p> <p>1 x PCIe x16 slot (Gen5 x8 link, LP, HL)</p> <p>1 x OCP3.0 socket (Gen5 x16 link)</p>		
Storage	<p><b>w mid-bay</b> Front bays: 12 x 2.5" Hot-Swap drive bays 12 x SATA/SAS/NVMe Mid-bay: 4 x 2.5" storage bays support NVMe /SATA</p> <p>*SAS support only from optional SAS HBA/RAID card **Internal Storage Bays is designated as build-to-order only, owing to quality or installation concerns.</p> <p><b>w/o mid-bay</b> Front bays: 12 x 2.5" Hot-Swap drive bays 12 x SATA/SAS/NVMe</p> <p>*SAS support only from optional SAS HBA/RAID card</p>	<p>Front bays: 4 x 3.5"/2.5" Hot-Swap drive bays Support up to 4 x SATA/SAS/NVMe*</p> <p>*SAS support only from optional SAS HBA/RAID card *MCIO CABLE is required to support NVMe hard drives</p>	<p>Front bays: 4 x 2.5" Hot-Swap drive bays Support up to 4 x SATA/SAS /NVMe*</p> <p>*SAS support only from optional SAS HBA/RAID card</p>
NIC	<p>2 x 1GbE RJ45 onboard LAN ports (Intel i350-AM2 controller)</p> <p>2 x 10Gb OCP Card (Optional)</p> <p>1 x Management LAN</p>		

\* The total number of NVMe drives installed will affect the total number of GPUs that can be installed.